



## POLYSTEEL SHOPPING TROLLEYS - STANDARD LINE

CAPACITY liters	LENGTH mm.	WIDTH mm.	HEIGHT mm.	WHEEL	WEIGHT KG.	NESTABILITY mm.	X 5 TROLLEYS mts.	X 10 TROLLEYS mts.	X 15 TROLLEYS mts.	X 25 TROLLEYS mts.
<b>90</b>	906	598	995	Ø 125 - TYPE 3	15.8	230	1.83	2.98	4.13	6.47
				Ø 125 - TYPE 6	16.1					
				Ø 125 - TYPE 8	15.8					
<b>110</b>	1105	598	995	Ø 125 - TYPE 3	17.5	230	2.02	3.17	4.32	6.62
				Ø 125 - TYPE 6	17.8					
				Ø 125 - TYPE 8	17.5					
<b>140</b>	933	601	995	Ø 125 - TYPE 3	18.1	255	1.95	3.22	4.50	7.05
				Ø 125 - TYPE 6	18.4					
				Ø 125 - TYPE 8	18.1					
<b>140</b> FOR CRATES	933	597	1105	Ø 125 - TYPE 3	20.2	255	1.95	3.22	4.50	7.05
				Ø 125 - TYPE 6	20.5					
				Ø 125 - TYPE 8	20.2					
<b>160</b>	1082	601	995	Ø 125 - TYPE 3	18.9	255	2.10	3.38	4.65	7.20
				Ø 125 - TYPE 6	19.2					
				Ø 125 - TYPE 8	18.9					
<b>160</b> FOR CRATES	1082	597	1105	Ø 125 - TYPE 3	21.3	255	2.10	3.38	4.65	7.20
				Ø 125 - TYPE 6	21.6					
				Ø 125 - TYPE 8	21.3					
<b>195</b>	1006	598	1054	Ø 125 - TYPE 3	19.7	255	2.03	3.30	4.58	7.13
				Ø 125 - TYPE 6	20.0					
				Ø 125 - TYPE 8	19.7					
<b>220</b>	1125	598	1054	Ø 125 - TYPE 3	21.1	255	2.14	3.42	4.69	7.24
				Ø 125 - TYPE 6	21.4					
				Ø 125 - TYPE 8	21.1					
<b>242</b>	1235	598	1054	Ø 125 - TYPE 3	22.6	255	2.25	3.53	4.80	7.35
				Ø 125 - TYPE 6	22.9					
				Ø 125 - TYPE 8	22.6					